

EACOME BC400	
<b>Model</b>	EACOME BC400
<b>Name</b>	USB2.0 HD Video Conference Camera
<b>Camera</b>	
Video System	1080P, 720P, 540P, 480P, 360P, 240P etc.
Sensor	1/2.7", CMOS, Effective Pixel: 2.07M
Scanning Mode	Progressive
Lens	12x, f3.5mm ~ 42.3mm, F1.8 ~ F2.8
Digital Zoom	16x
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, Indoor, Outdoor, One Push, Manual, VAR
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Horizontal Angle of View	72.5° ~ 6.9°
Vertical Angle of View	44.8° ~ 3.9°
Horizontal Rotation Range	±170°
Vertical Rotation Range	-30°~+90°
Pan Speed Range	1.7° ~ 100°/s
Tilt Speed Range	1.7° ~ 69.9°/s
H & V Flip	Support
Image Freeze	Support
Number of Preset	255
Preset Accuracy	0.1°
<b>USB Featured</b>	
Operate System	Windows 7, Windows 8, Windows 10, Mac OS X,
Color System / Compression	YUV 4:2:2 / H.264 / MJPEG
Video Format	YUY2 (ISOC): max to 640x480P@30fps H.264 AVC: max to 1080P@30fps MJPEG: max to 1080P@30fps
Audio on USB	Support
USB Video Communication Protocol	UVC 1.1
UVC PTZ	Support
<b>Generic Specification</b>	
Input Voltage	DC 12V
Current Consumption	1.0A (Max)
Operating Temperature	-10°C ~ 40°C (14°F ~ 104°F)
Storage Temperature	-40°C ~ 60°C (-40°F ~ 140°F)
Power Consumption	12W (Max)
MTBF	>30000h
Size	144mm x 144mm x 167.9mm
Net Weight	1.35Kg
Picture	